



MORBARK®
BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES



MORBARK® BEEVER™ M15RX CHIPPER

MODELS

M8D
M12D
M12R
M15R
M15RX
M18R
M18RX
M20R

HIGH CAPACITY AND LIGHTER WEIGHT, IDEAL FOR RESIDENTIAL TREE SERVICES, UTILITY LINE CLEARING, VEGETATION MANAGEMENT, MAINTENANCE CONTRACTORS AND MUNICIPALITIES

MORBARK® BEEVER™ M15RX CHIPPER



BENEFITS

- With its high capacity and lighter weight design, this compact chipper is the ideal unit for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- Hydra-Lift top feed wheel compression system with spring-assisted down pressure provides more than 1,500 lbs. of material crushing power.
- Like all Morbark equipment, the M15RX is a long-lasting, durable machine backed by a world-class parts and service support team.



TorqMax™ Feed System

The powerful TorqMax™ top feed wheel compression system generates more than 3,400 lb./ft. of material pulling force.



Infeed System

The wide infeed opening with 18" diameter single top feed wheel and straight flow-through infeed easily climbs over material, reduces drag and increases chipping efficiency.



Channel Frame

The 8.2 lb., 6" channel frame rails with 2" x 6" tubular steel frame with cross bracing increases structural strength while maintaining low unit weight.



360° Swivel Discharge

360° manual crank swivel discharge with adjustable height puts chips right where they're needed without removing the Beever from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/23/14

General

Chipping capacity 15"
 Height 8'4"
 Width 6'10 5/8"
 Length 16'5"
 Weight (approximate). 6,100 lbs.
 Suspension. 7,000 lb. torsion
 Infeed opening. 55 1/2" wide x 34" high
 Throat opening. 20 1/2" wide x 15" high
 Drum 23 3/4" wide x 21 3/8" diameter
 Engine. . . CAT, Cummins, GM, John Deere, Perkins
 Horsepower 80–142 HP
 Fuel capacity 32 gallons
 Hydraulic capacity 13 gallons
 Frame 8.2 lb., 6" channel
 Tires. (2) 215/75R17 1/2"
 Hitch 2 1/2" Pintle

Equipment Highlights

21 3/8" diameter x 23 3/4" wide staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided, chambered air impeller systems
 Single (top) horizontal feed wheel with TorqMax top feed wheel compression system, hydraulic lift assist, spring-assisted down pressure and manually applied hydraulic down pressure at the valve handle
 Reversing automatic feed system
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
 Fuel tank sight gauge, drain plug and shut-off valve
 Hydraulic tank shut-off valve, drain plug and clean-out cover

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe™ Operator Safety Shield
 Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
 Custom paint and logo packages
 Bottom Bump Bar
 Hydraulic Swivel Discharge
 Cone Holder
 Spare Tire/Mount
 Folding Infeed Tray
 Bottom Feedwheel
 Flow Control
 Axle, Fender and Battery Box Options Available



MORBARK®
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

12 Andrew Baxter Drive
 Airport Oaks, Auckland 2022
 New Zealand

Tel +64 (0)9 275 0443
 sales@commercialoutdoormachinery.co.nz
 www.commercialoutdoormachinery.co.nz

www.morbark.com

**SOLD & SERVICED
 IN NEW ZEALAND BY**

