



MORBARK®
BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES



MORBARK® BEEVER™ M15R TRACK

MODELS

M8D
M12D
M12R
M15R
M15R TRACK
M15RX
M18R
M18RX
M20R

A POWERFUL, EASILY TRANSPORTABLE, COMPACT AND ECONOMICAL CHIPPER. IDEAL FOR UTILITY LINE CLEARING, RESIDENTIAL TREE SERVICES, RENTAL YARDS AND MUNICIPALITIES

MORBARK® BEEVER™ M15R TRACK



BENEFITS

- Ideal for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities, this high-capacity, high-production chipper includes more standard features than any other chipper in its class.
- The powerful TorqMax™ dual feed wheel compression system generates more than 6,600 lb./ft. of material pulling force.
- Unit is pre-plumbed and outfitted for the easy installation of most aftermarket components.
- Ergonomic infeed design provides consistent feed control bar activation.
- Like all Morbark equipment, the M15R is a long-lasting, durable machine backed by a world-class parts and service support team.



Drum

30" diameter four-knife staggered-knife-pocket drum with patented removable knife holders provides maximum chipping efficiency.



Track Undercarriage

Take the chipper to the material with 400mm rubber tracks, 4.84 PSI ground pressure, low-speed and high-speed travel ranges of 1.0 MPH and 1.8 MPH.



Reversing Auto-feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,500 lbs. of perpetual down pressure.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 2/9/16

General

Chipping capacity 18"
 Height 8'6"
 Width 7'10"
 Length 16'
 Gross weight (approximate) 13,500 lbs.
 Infeed opening 56" wide x 37" high
 Throat opening 20½" wide x 18" high
 Drum 23 ¾" wide x 30" diameter
 Engine Tier 4i
 Horsepower 147–174 HP
 Fuel capacity 32 gallons
 Hydraulic capacity 26 gallons
 Frame 6" x 2" x ¼" wall tube
 Tracks Rubber Track Undercarriage

Equipment Highlights

Wireless Remote Control operation with tethered back-up system controls the track functions, feed functions, yoke functions and throttle functions with emergency engine stop
 Dual horizontal feed wheel compression system with hydraulic lift assist, spring-assisted down pressure and manually applied hydraulic down pressure at the valve handle
 Reversing automatic feed system
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
 Fuel tank sight gauge, drain plug and shut-off valve
 Hydraulic tank shut-off valve, drain plug and clean-out cover
 Live hydraulics; ball valve, pump, motor, control valve and variable speed flow control

Additional Features

Steel guard enclosing valve bank and automatic feed system components
 Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
 Custom paint and logo packages
 Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
 Bottom Bump Bar
 Hydraulic Swivel Discharge Chute
 Folding Infeed Tray
 Flow Control
 Battery Box Options Available



Commercial
Outdoor
 Machinery

16 Andrew Baxter Drive
 Airport Oaks,
 Auckland 2022
 New Zealand

Tel +64 (0)9 275 0443
 sales@commercialoutdoormachinery.co.nz
 www.commercialoutdoormachinery.co.nz
 www.morbark.com

ASK FOR AN ONSITE DEMONSTRATION – SEE MORBARK OUTPERFORM THE COMPETITION