

HUSTLER® COMMERCIAL ZERO-TURN MOWER

X-ONE®

BUILT FOR ALL DAY, EVERYDAY PERFORMANCE



A PERFECT BLEND OF POWER, VERSATILITY AND COMFORT

The X-ONE® is built for the full-time commercial landscaper to provide all day, everyday performance. It offers a choice of side or rear-discharge decks, and with an 44.3 litre gas tank, and speeds of over 16 km per hour, you can cover a lot of ground in less time.

The X-One sets the standard for commercial zero-turn value.



INCREDIBLE POWER

Driven by Parker unitized pumps and choice of engine sizes.



ADDED VERSATILITY

Choice of 4 cutting widths plus side or rear discharge decks.



UNMATCHED COMFORT

Internal suspension seat with operator isolator and armrests standard.



LIMITED
LIFETIME WARRANTY
FRAME & LEADING EDGE OF DECK

LIMITED WARRANTY
2 YEAR
NO HOUR LIMIT

OR

LIMITED WARRANTY
5 YEAR
500 HOUR

Find A Hustler Dealer
visit www.hustlermowers.co.nz

ENGINE

Manufacturer	Kawasaki FX730V, FX850V
HP	54"RD, 60"RD deck: 23.5HP* - FX730V 52", 60" deck: 27HP* - FX850V * Per SAE J1995
Displacement	FX730V: 726cc FX850V: 852cc
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	3 year

DRIVE SYSTEM

Type	Dual hydrostatic
Transmissions	Parker unitized 12cc/rev pump & 15.9ci/rev wheel motors
Hydraulic Cooling	Transmission mounted fans
Speed	10.5 mph (16.9 kph)
Parking Brakes	Patented automatic

DECKS

Cutting Width	Side discharge: 52", 60" Rear discharge: 54", 60"
Cutting Heights	1" - 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	52" deck: 3 - 17.86" x 2.5" x .20" 54" RD deck: 3 - 18.5" x 2.5" x .20" 60", 60" RD deck: 3 - 20.5" x 2.5" x .20"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	10 ga. Fab. with 7 ga. wrappers
Spindle Mounts	52", 60": 10 ga. with 7 ga. doubler, steel 54" RD, 60" RD: 10 ga. + large 11 ga. doubler, steel
Impact/Trim Areas	11 ga. formed channel with rolled edge

CONSTRUCTION

Frame	1.5" x 3.0" x .188" steel
Front Caster Wheels	Mounted with sealed ball bearings
Front Caster Forks	Fabricated 1/2" steel

GENERAL

Seat	Bolstered internal suspension seat with 4 point rubber isolation mounts
Fuel Capacity	11.7 gallons (44.3L)
Cup Holder	Yes
Front Tire	13 x 6.5 - 6
Drive Tire	52", 54" RD deck: 24 x 9.5 - 12 60", 60" RD deck: 24 x 12 - 12

DIMENSIONS

Weight	52": 1244 lbs (564.3 kg) 54" RD: 1265 lbs (573.8 kg) 60", 60" RD: 1282 lbs (582.5 kg)
Height w/rops up	71.6" (1.82m)
Height w/rops Folded	49" (1.24m)
Length	52", 60" deck: 82.75" (2.10m) 54" RD, 60" RD deck: 86.25" (2.19m)
Width	52" deck: 54.4" (1.38m) 54" RD deck: 55.72" (1.42m) 60" deck: 62.4" (1.58m) 60" RD deck: 61.72" (1.57m)
Tire Width	52", 54" RD deck: 51" (1.30m) 60", 60" RD deck: 54.5" (1.38m)

PRODUCTIVITY*

Acres Per Hour	52": 5.52	54"RD: 5.73
	60": 6.36	60"RD: 6.36

OPTIONAL ACCESSORIES

Semi pneumatic front tires	FlexForks™
Steering lever extension kit	Mulch kit
Deck rear anti-scalp wheels	Light kit
3-bag grass catcher kit (12 bushels)	Stripe kit
Mesh side bagger (3 bushels)	Electric deck lift
Metal side bagger (3.5 bushels)	BacVac powered catcher kit

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

X-ONE | AT A GLANCE

- 52" or 60" commercial-style, side-discharge deck
- 54" or 60" rear-discharge deck
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak™ steering – responsive, precise control
- Patented automatic park brake
- High horsepower and varied engine options
- Clean and simple design
- 13" front and 24" drive tires



Visit hustlermowers.co.nz
and try our compare products tool!